

# DA-A35 SERIES High Efficiency CoB Recessed down light

Catalog No. \_\_\_\_\_




Date \_\_\_\_\_

Type \_\_\_\_\_




Project \_\_\_\_\_






DA-A35D



DA-A35C



DA-A35N



## Accessories



DA-A35-IP COVER  
For IP 44 rating



LSC9W500P-UNI

- Optional IP cover use with DA-A35N
- Optional IP cover use with DA-A35D
- IP-44 rated
- Driver with molex direct connection
- 9W 500mA
- 120-277V input, UL listed
- (Other drivers and connections available)

## Ordering Code

DA-A35D	Gimbal fixture 350mA~700mA
DA-A35C	Deep Cone fixture 350~700mA
DA-A35N	Down Light low profile 350~700mA
IP-Cover	Clear IP-cover lens for D & N models
LSC9W500P	120~277V 9W 500mA driver (UL)
DA-A35-R40	40 degree reflector for all models

## Description

DA-A35 series LED recessed down light is a constant current design can use with 350mA 500mA or 700mA driver. Heat sink design to use best with 500mA driver shown above. Using CoB chips available with 3000K, 4000K & 5000K. Dimmable driver available by others. Max rated output: 350mA is 500 lumens, 500mA is 700 lumen. 700mA is 900 lumens. 80+ CRI standard (Optional 90+ CRI is available). ETL listed for USA & Canada.

## LED Performance

- LED:** CoB
- SDCM:** 3 Step Macadam Elipse
- CCT:** 3000K (WW), 4000K (NW), 5000K (CW)
- CRI:** >80 Typically 83 (Optional 90+ CRI is available)
- LIFE:** 70% of initial lumens after 50,000 hrs

**Warranty:** 5 Year Limited Fixture Warranty

## Ordering Codes

Follow the steps to specify your fixture. To order DA-A35D CRI80 white fixture in 3000K

example: **DA-A35D WU 830**

① Base Code	② Product Code	③ Code Colour	④ Code CRI.	⑤ Code Temperature										
DA-A35	D	WU	<table border="1"> <tr><td>8</td><td>80+</td></tr> <tr><td>9</td><td>90+</td></tr> </table>	8	80+	9	90+	<table border="1"> <tr><td>30</td><td>3000K</td></tr> <tr><td>40</td><td>4000K</td></tr> <tr><td>50</td><td>5000K</td></tr> </table>	30	3000K	40	4000K	50	5000K
8	80+													
9	90+													
30	3000K													
40	4000K													
50	5000K													

## Technical Specs

- Typical 7.5W 500mA
- Typical 700 lumens @ 500mA
- High Output CoB LED
- Front glass lens & user changeable reflector.
- Specify Driver separately
- 80+ or 90 + CRI
- Included: 25 degrees reflector, 40 degrees reflector available

## Optional Accessories

- IP-Cover lens for DA-A35N & D
- LED Drivers range from 350mA ~ 700mA
- Dimmable LED drivers available consult factory
- User interchangeable 40 degrees reflector for all models.